



# ADC AD-236

AD-236 Specifications				
Maximum Capacity (dry weight) per pocket	30 lb	13.6 kg		
Tumbler Diameter	27-1/4	69.22 cm		
Tumbler Depth	30	76.2 cm		
Tumbler Volume per pocket	10.1 cu ft	286 L		
Tumbler / Drive Motor per pocket	1/2 hp	0.373 kW		
Blower / Fan Motor per pocket	1/2 hp	0.373 kW		
Door Opening (diameter)	21-1/2	54.61 cm		
Door Sill Height top pocket / bottom pocket	51-1/4 / 13-1/2	130.2 cm / 34.3 cm		
Water Connection	N / A			
Dryers per 20ft Container	11 / 22			
Dryers per 48ft Container	30 / 33			
GAS MODEL	Voltage Available	120-480V	1,3ø 2,3 50/60 Hz	
	Approximate Net Weight	850 lb	385.5 kg	
	Approximate Shipping Weight	900 lb	408.2 kg	
	Airflow per pocket	60 Hz	400 cfm	11.33 cmm
		50 Hz	333 cfm	9.44 cmm
	Heat Input per pocket	80,000 Btu/hr		20,160 kcal/hr
	Exhaust Connection (diameter)	8	20.32 cm	
Compressed Air Connection	N / A			
Compressed Air Volume	N / A			
Inlet Pipe Connection	3/4" M.N.P.T.			
ELECTRIC MODEL	Voltage Available	N / A		
	Approximate Net Weight	N / A		
	Approximate Shipping Weight	N / A		
	Airflow per pocket	N / A		
	Exhaust Connection (diameter) per pocket	N / A		
	Compressed Air Connection	N / A		
	Compressed Air Volume	N / A		
STEAM MODEL	Oven Size			
	kW	BTU/Hr	Kcal/Hr	
	Voltage Available	N / A		
	Approximate Net Weight	N / A		
	Approximate Shipping Weight	N / A		
	Airflow per pocket	N / A		
	Steam Consumption per pocket	N / A		
Operating Steam Pressure	N / A			
Exhaust Connection (Diameter) per pocket	N / A			
Compressed Air Connection	N / A			
Compressed Air Volume	N / A			
Boiler Horsepower (Normal Load) per pocket	N / A			
Supply Connection per pocket	N / A			
Return Connection per pocket	N / A			

Electrical Specs listed are per pocket

3/16

Electrical Service Specifications					
GAS ONLY					
SERVICE VOLTAGE	PHASE	WIRE SERVICE	APPROX AMP DRAW		CIRCUIT BREAKER
			60 Hz	50 Hz	
120	1	2	8.7	--	15
208	1	2	5.2	--	15
240	1	2	4.8	4.7	15
208	3	3	3.0	--	15
240	3	3	3.2	--	15

