ADC AD-24

20-lb Capacity Coin Dryer

Standard Features:

- 20-lb. capacity
- 8.10 cu. ft. basket volume
- 60,000 Btu/hr heat input, 400 cfm airflow
- Radial airflow
- Steel door with gasketless glass
- Only 28-1/2"Wide
- Available in gas and electric heat



Why Purchase ADC AD-24?

AD-24 Coin Dryer

Engineer-Driven Design That is Built to Last

Our dryers showcase ADC's engineer-driven approach to design. Bearings are permanently lubricated on the motor and drive system. There are no chains used at ADC; rather, we use V-belts and pulleys for smooth, quiet, and trouble-free operation. Our dryer cabinets are electrostatically powder-painted inside and out, then baked at 420-degrees fahrenheit before final assembly—ensuring the hardest surface and the longest-lasting finish in the industry.

Rugged Steel Door with Gasketless Door Glass

Our dryer doors are one solid piece of steel with gasketless glass. This eliminates the issue of glass falling out due to wear and tear on rubber gaskets that some manufacturers use to secure their glass. The security and durability that gasketless glass provides is essential to a successful laundromat operation.

Easy-to-Read, Multilingual Controls

We were the first to bring computer-operated dryers to the market and today we continue to be a leader in applying technology to dryer operation. Our years of experience along with our accessible design, easy-to-read LCD screens and our user-friendly multilingual interface positions ADC as the pioneer in the laundry industry.


Your local ADC independent authorized distributor



www.adclaundry.com


ADC AD-24

AD-24 Specifications							
Tumbler Capacity (dr	20 lbs. (9.07 kg)						
Tumbler Diameter	27-1/4" (69.22 cm)						
Tumbler Depth	24" (60.96 cm)						
Tumbler Volume		8.10 cu ft (229.37 L)					
Tumbler/Drive Motor		1/2 hp (0.37 kW)					
Blower/Fan Motor		N/A					
Door Opening (Diam	21-1/2" (54.61 cm)						
Door Sill Height		28-1/3" (71.91 cm)					
S.A.F.E. Water Connec	tion	3/4" F.N.P.T.					
Dryers per 20'/40' Co	14/30						
Dryers per 48'/53' Tru	ck	42 / 48					
Width		28-1/2" (72.39 cm)					
Depth		36-5/8" (93 cm)					
Height		65"(165.1 cm)					
Airflow gas/electric	60 Hz 50 Hz	400 cfm (11.33 cmm) 333 cfm (9.44 cmm)					
Exhaust Connection		6" (15.24 cm)					
GAS MODEL:	Approx. Net Wt. Approx. Ship Wt. Heat Input et Pipe Connection	426 lbs (193.23 kg) 461 lbs (209.11 kg) 60,000 btu/hr (15,120 kcal/hr) 1/2" M.N.P.T.					
	Approx. Net Wt. Approx. Ship Wt. nection (diameter) n Size per pocket Btu/hr (kcal/hr) 61,400 (15,500) 68,200 (17,200) 81,900 (20,600)	426 lbs (193.23 kg) 461 lbs (209.11 kg) 6" (15.24 cm)					



36 5/8

[93]



REAR VIEW (GAS AND ELECTRIC)

* Not available in steam.

** Specifications in parentheses are metric equivalents.

Electrical Service Specifications									
GAS									
SERVICE VOLTAGE	PHASE	WIRE SERVICE	APPROX AMP DRAW		CIRCUIT				
			60 Hz	50 Hz	BREAKER				
120	1ø	2	8.7		15				
208	1ø	2	5.2		15				
240	1ø	2	4.8	5.8	15				
208	3ø	3	3.0		15				
240	3ø	3	3.2	3.6	15				
380	3ø	4*		2.2	15				
400	3ø	4*		2.2	15				
416	3ø	4*		2.3	15				
460	3ø	3	2.1		15				
480	3ø	3	2.1		15				

* 3-wire is available.



Electrical Service Specifications								
18 kW Electric								
SERVICE	PHASE	WIRE SERVICE	APPROX AMP DRAW		CIRCUIT			
VOLTAGE	E		60 Hz	50 Hz	BREAKER			
208	1ø	2	92		125			
240	1ø	2		81	110			
240	1ø	2	80		100			
208	3ø	3	55		70			
240	3ø	3	48		60			
20 kW Electric								
208	1ø	3	101		150			
240	1ø	2	88		110			
24 kW Electric								
208	3ø	3	72		90			
240	3ø	3	63		80			
416	3ø	4*		39	50			
460	3ø	3	32		40			
480	3ø	3	31		40			

QY160022 1/17 88 Currant Road, Fall River, MA 02720-4781 • 508.678.9000

www.adclaundry.com

10/04/06