

MDG30PCCWW

MAYTAG® COMMERCIAL
MULTI-LOAD DRYER



LEGENDARY MAYTAG DEPENDABILITY

Maximizing your equipment investment for over a half century.



HANDLES MORE LAUNDRY AT ONCE

Designed to match double and triple loads from front-load washers or dry big, bulky items. Plus, the extra-large door opening makes loading and unloading easy.

MICROPROCESSOR CONTROLS

Programmable controls let you adjust pricing at the touch of a button. The microprocessor coin-drop helps prevent slugging and the optional audit system matches cycles used to coins collected for additional accountability.

FOR YOUR CUSTOMERS:

- Large 30-Pound Capacity
- One Touch Selects Drying Temperature
- Digital Display Shows Time Remaining In Cycle
- Extra-Large Door Opening

FOR YOUR OPERATION:

- Extra-Large Security Coin Vault
- Extra-Large Lint Compartment
- Easy-Access Design For Self-Service

BUILT-TO-LAST™ FEATURES:

- Sealed Bearings Never Need Lubrication
- Heavy-Duty Motor
- 5-Year Limited Warranty—All Parts Covered



LARGE CAPACITY
LETS YOU SERVE MORE CUSTOMERS

LAUNDRY SOLUTIONS
YOU CAN *DEPEND ON.*

visit maytagcommerciallaundry.com
or call 800-662-3587



OUR COMMITMENT TO DEPENDABLE QUALITY

At Maytag, we believe durable goods should remain just that. That's why every Maytag® product is constructed of the highest-quality materials and with the utmost in precision craftsmanship. It's also why we stand behind our equipment with solid service and support from our professional Maytag laundry suppliers. Simply put, when you choose Maytag® products, you ensure your peace of mind.




MDG30PCCWW MAYTAG® COMMERCIAL MULTI-LOAD DRYER

Maytag® Commercial Multi-Load Dryer MICROPROCESSOR COIN-DROP

DRYER SPECIFICATIONS	
MODEL	MDG30PCCWW
TUMBLER	
Capacity — lbs. (kg)	30 (13.6)
Capacity — cu. ft. (cu. m)	12.3 (.348)
Diameter — in. (mm)	30 (762)
Depth — in. (mm)	30 (762)
DRIVE MOTOR	
HP (kw)	1/2 (.373)
AIRFLOW	
Cfm (cmm)	600 (17)
HEAT INPUT	
BTU/hr. (kcal/hr.)	90,000 (22,680)
GAS INLET	
In. (cm)	1/2 (1.3)
VOLTAGE/BREAKER SIZE — amps	
120V/1 PH	20
COLOR	
White	•
Bisque	•
APPROXIMATE WEIGHT	
Crated — lbs. (kg)	550 (249)
Uncrated — lbs. (kg)	500 (227)
DIMENSIONS	
A) Height — in. (mm)	72 (1829)
B) Width — in. (mm)	31 3/8 (797)
C) Depth including door handle — in. (mm)	43 (1092)
D) Floor to center of exhaust — in. (mm)	20 1/4 (514)
E) Exhaust diameter — in. (mm)	8 (203)*
Door opening — in. (mm)	21 1/2 (546)

*Requires 8" (203 mm) material if venting horizontally; 10" (254 mm) if venting vertically.

See specific instructions for proper installation.
Because of continuous product improvement, Maytag reserves the right to change specifications without notice.



NEW YORK CITY
M.E.A.



5-YEAR LIMITED WARRANTY ALL PARTS COVERED

For a period from the date of original purchase through the time listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage. See complete warranty for details.