



END LOADER

Washer/Extractor



U.S.A.

ISO 9001 Certified

All Braun Products are Proudly
Manufactured in the U.S.A.

gabraun.com

END LOADER

STANDARD MODELS

- Available in processing capacities of 100, 200, 300, and 400 lbs. dry weight load sizes
- Ideal for low ceiling installations and washrooms with limited space
- Strength and durability – the highest quality materials and simple, rugged design make this a truly heavy duty machine. The Braun End Loader will operate for decades
- Thorough wash action and high-speed extraction assure high-quality washing

CONTROL PANEL

Standard on all Braun End Loader machines, touch screen controls are simple, intuitive, easy to use, and control all major machine functions.

AUTOMATIC SAFETY AND AUTO LOAD REBALANCE TECHNOLOGY

Optical sensors on Braun End Loaders will instruct the machines to:

- Automatically shut down if they are out of balance
- Automatically balance loads prior to moving into the extraction phase to evenly distribute wet goods against the cylinder, eliminating the need for artificial counterbalances.



BRAUN'S NEUTRON SUSPENSION

- Unsurpassed vibration dampening allows for installation without a foundation, even on upper floors that can hold the static weight of the machine!
- Isolates vibration from the workspace
- Promotes less wear on major end components for exceptional durability and machine longevity
- Provides for consistent wash performance

Specifications

End Loader Model	Max. Recommended Capacity – Lbs./Kg.	Cylinder Dia. X Depth – Inches/mm	Cylinder Volume – Cubic Ft./Cubic Meters	No. of Pockets	Cylinder Door Area Open for Loading – Sq. Inches/Sq. cm	Hgt. of Unloading Doors Above Floor – Inches/mm	Extract Motor – H.P.	Extract Speed – R.P.M.	Wash Motor – H.P.	Wash Speed – R.P.M.	Balance Motor – Speed	Drain Valve – Inches	Automatic Inlet Valves – Inches/mm	Steam Valve – Inches/mm	Overall Width w/Dispenser – Inches/mm	Overall Depth w/Dispenser – Inches/mm	Overall Height w/Dispenser - Inches/mm	Approx. Domestic Shipping Wt. (Net) – Lbs./kg. skidded	Approx. Export Shipping Wt. – Lbs./kg.	Export Cubage – Cubic Ft./Cubic Meters
Neutron 100-2	130 59	37 x 34 940 x 864	21.2 0.600	2	236 1,523	37.5 953	7.5	UP	1.5	UP	UP	6 152	2 51	3/4 19	62 1,581	64 1,626	73 1,855	3,850 1,746	3,850 1,746	171 4.79
Neutron 200-2	230 105	44 x 42 1,118 x 1067	36.9 1.045	2	297 1,916	37.5 953	10	UP	3	UP	UP	6 152	2 51	3/4 19	73 1,855	75 1,905	73 1,855	5,720 2,594	6,850 3,107	318 9.01
Neutron 300-3	350 159	54 x 42 1,372 x 1067	55.6 1.575	3	420 2,710	41.5 1,040	15	UP	5.4	UP	UP	6 152	2 51	3/4 19	101 2,565	84 2,133.6	85 2,160	9,475 4,297	11,275 5,113	506 14.32
Neutron 400-3	450 204	60 x 44 1,524 x 1118	71.9 2.036	3	464 2,994	44 1,118	20	UP	7.5	UP	UP	8 203	2 51	1 1/4 32	108 2,743	88 2,235.2	91 2,311.4	12,780 5,796	14,500 6,576	575 16.28

UP = User Programmable



ISO 9001 CERTIFIED

G.A. Braun, Inc.
79 General Irwin Boulevard
N. Syracuse, NY 13212

Mail to:
P.O. Box 3029
Syracuse, NY 13220-3029

Phone
1-800-432-7286

Fax
(315) 475-4130

Parts Help Desk
1-800-432-7286 X 1

Service Help Desk
1-800-432-7286 X 2



U.S.A.

All Braun Products are Proudly
Manufactured in the U.S.A.